# **Lateral Plungers •** smooth, without seal, with female thread 22150.1042



## **Product Description**

To be used for positioning and applying pressure, e.g. during painting and sandblasting.

#### **Material**

# Body

- Aluminium Al
- Threaded washer
- Steel, blackened

#### Spring

• Steel, zinc-plated by galvanization

#### Assembly

```
Formula for calculating the center distance for
the mounting hole:
l_0 = z/2 + w + x,
l_0 = center distance,
y = workpiece height,
w = workpiece height,
x = stroke,
z = stop diameter
Calculation dimension x for workpieces:
x = d_2/2 - s
```

Installation by pressing in.

## Characteristic

Version heavy spring load = spring from steel, zinc-plated by galvanization

#### More information


# Notes


Individual set screws can be screwed in the plate with threaded hole.

### **Further products**

• Eccentric Mounting Bushings, for lateral plungers, smooth

#### Drawing





#### **Order information**

Dimens	sions	Spring load			Dimensions			Stroke	Location	ß	<b>I</b>	Art. No.	
d₁	d <sub>2</sub>	F max. <sup>1)</sup> ~	d₃	l <sub>1</sub> -1	l <sub>2</sub>	I <sub>3</sub>	I <sub>4</sub>	S	hole D H8	max.	-		
[mn	n]	[N]			[mm]			[mm]	[mm]	[°C]	[g]		
Heavy sprin	ng load												
16	M6	200	10.2	18	16.7	7.5	1.7	1.6	16	250	9.3	22150.1042	

1) statistical average value

## Accessories

assembly tool	Dimensions d <sub>1</sub> [mm]	<b>a</b> [9]	Art. No.
	16	105	22150.0833

# Compliance

#### **RoHS compliant**

Compliant according to Directive 2011/65/EU and Directive 2015/863.

## Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

### Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.