Lateral Plungers • with plastic spring and pin - INCH 2B150.0231



Product Description

To be used for positioning and applying pressure, e.g. during painting and sandblasting.

Material

- Body
- Aluminium AI
- Spring
- plastic


Pin

Steel, case-hardened, blackened

Assembly

Installation by pressing in. Formula for calculating the center distance for the mounting hole: $I_0 = z/2 + w + x$, I_0 = center distance, y = workpiece height, w = workpiece length, x = coordinate dimension, s = stroke, z = stop diameter Calculation dimension x: y greater than or equal to $I_2 - d_2/2$, then $x = d_2/2 - s$ or y smaller than $I_2 - d_2/2$, then x = $d_2/2 - s - [(l_2 - d_2/2 - y) * 0,123]$ Characteristic Version heavy spring load = green spring

Drawing



*some sizes (see chart) have a deviating pin shape

Order information

Dimensions		Spring load	Dimensions		Stroke	Location	x ²⁾		Ĭ	Art. No.
d1	d ₂	F max. ¹⁾ ~	Ι ₁ -0.03	Ι 2 ±0.02	s	hole D H8		max.	_	
[in]		[lb]	[ir	ן]	[in]	[in]	[in]	[°F]	[oz]	
Pin: Steel/H	leavy spring load	ł								
1/2	0.315	22.2	0.553	0.515	0.024	0.5	0.134	212	0.262	2B150.0231

1) statistical average value

²⁾ If the workpiece height (y) is less than I2-d2/2, the coordinate dimension (x) must be calculated.

Accessories

	Dimensions d ₁ [in]	[02]	Art. No.
assembly tool	1/2	2.321	22150.0832

Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.