

Spring Plungers • with ball and internal hexagon
22030.0004



Product Description

Spring plungers can be used for locating or for applying pressure, as a detent or for ejection.

Material

- Body**
- Free cutting steel, blackened
- Ball**
- Ball-bearing steel, hardened
- Spring**
- Stainless steel

Characteristic

Standard spring load: no marking



Standard spring load



Heavy spring load

More information


Notes

Special types on request.
Spring plungers are specially tested for spring range and forces.



References

Thread lock on request, please refer to appendix - Technical Data -
Calculation of indexing resistance, please refer to appendix - Technical Data -

Drawing



Order information

| Dimensions | | | WS | Stroke s | Spring load ¹⁾ | |  |  | Art. No. |
|--|----------------|----|------|-------------|---------------------------|---------------------|---|---|------------|
| d ₁ | d ₂ | l | | | F ₁ ~ | F ₂ ~ | max. | | |
| [mm] | | | [mm] | [mm] | [N] | | [°C] | [g] | |
| free cutting steel, standard spring load | | | | | | | | | |
| M4 | 2.5 | 12 | 2 | 0.8 | 8.5 | 14 | 250 | 0.6 | 22030.0004 |

¹⁾ statistical average value

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances



Lead can cause cancer and reproductive harm from exposure
<https://www.P65Warnings.ca.gov/>

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.