

## Index Plungers • with hexagon collar

22120.0030



## Product Description

Index plungers are used for indexing bores.

## Material

## Body

- Free cutting steel, blackened

## Locking pin

- Steel, hardened

## Assembly

The screw length can be adapted by distance collars for index plungers (EH 22120.).

## More information

## Notes


Knob not removable.

Lock nuts have to be purchased separately.


## Further products

- Mounting Blocks, for index bolts and index plungers, die-cast
- Locating Bushings, for index bolts and index plungers
- Distance Collars, for index plungers

## Drawing





## Order information


Dimensions								WS	Spring load <sup>1)</sup>				Art. No.
d <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	l <sub>2</sub> min.	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>	l <sub>6</sub> min.	F <sub>1</sub> ~	F <sub>2</sub> ~	max.			
-0.02													
-0.05													
[mm]								[mm]	[N]		[°C]	[g]	
without knob – picture 2, Free cutting steel													
10	M20 x 1,5	M8	10	33	10	12	30	22	23	54	250	97	22120.0030

<sup>1)</sup> statistical average value

Accessories

	Dimensions d <sub>2</sub> [mm]	Wrench size [mm]	 [g]	Art. No.
Lock nuts ISO 8675 (DIN 439), Steel				
	M20 x 1,5	30	32.0	22120.0120

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances



Lead can cause cancer and reproductive harm from exposure  
<https://www.P65Warnings.ca.gov/>

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.