# **Ball Lock Pins** • self-locking, with combination handle, precipitation-hardened 22380.0174



# **Product Description**

For quick fastening, locking, adjusting, changing and securing. Quickly and easily unlockable for frequently repeated connections.

All versions are corrosion resistant. When using stainless steel 1.4542: high-strength, hardened, abrasion resistant pin with high load capacity.

Ergonomic grip, different colour combinations available. The grip design provides protection of unintentional unlocking.

#### Material

#### Pin part

 Stainless steel 1.4542, precipitationhardened

#### Handle

• Thermoplastic PA 6 grey / orange

#### Spring

Stainless steel

# **Operation**

The balls are unlocked by pressing the button.

#### Characteristic

Types from stainless steel 1.4542 with marking below the balls.

#### More information

#### **Notes**

Special types on request.

# References

Stainless steel 1.4305, see EH 22370.

#### Accessories

Can easily be fitted with retaining cable EH 22400.

# **Further products**

- Ball Lock Pins, self-locking, with combination handle
- Locating Bushings, for ball lock pins and socket pins
- Locating Bushings, with flange, for ball lock pins and socket pins
- · Retaining Cables
- · Positioning Bushings, with collar, DIN 172 A
- Positioning Bushings, without collar, DIN 179 A

# **Drawing**



\*\* Types from stainless steel 1.4542 with marking

Erwin Halder KG

# **Order information**

Dimensions								Location	Shearing			I	Art. No.
<b>d</b> <sub>1</sub> -0.04 -0.08	l <sub>1</sub> +0.6	d <sub>2</sub>	d <sub>3</sub>	d₄	l <sub>2</sub> ±1	l <sub>3</sub>	I <sub>4</sub>	hole H11	resistance, two-shear <sup>1)</sup> min.	min.	max.		
[mm]								[mm]	[kN]	[°C]		[g]	
Handle colour: orange													
8	20	9.5	39.2	18.4	8.2	33.3	13.4	8	63	-30	80	40	22380.0174

<sup>1)</sup> Shearing resistance similar to DIN 50141

# **Application example**







# Compliance

# **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

# **Does not contain SVHC substances**

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

# Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

www.halder.com Page 3 of 3

Published on: 6.4.2024