# **Mounting Pads** • protected against slipping

22590 1210



# **Product Description**

Mounting pads can be used as foot or thrust pad. Not parallel bearing surfaces up to 15° degrees can be compensated.

The plastic cover on the mounting pad prevents slipping.

#### Motorial

### **Ball element**

· Stainless steel 1.4305

### Rubber cap

Rubber, black

# Pad


· Stainless steel 1.4305


### More information

#### Notes

For the versions  $d_1$  = M10 and M12 the lock nut conforms to DIN 934.

### **Drawing**





Order information

Dimensions					ws	Load capacity	Ĭ	Art. No.
d <sub>1</sub>	d <sub>2</sub>	h₁ ~	h <sub>2</sub>	t		for static load max.		
[mm]					[mm]	[kN]	[g]	
pad and ball element – picture 1, Stainless steel								
M10	36	26	11	9	17	16	74	22590.1210

### Compliance

### **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

## **Does not contain Proposition 65 substances**

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG www.halder.com Page 1 of 1