Push Plungers • with pin, protected against rotating

23230.0572



Product Description

The push plunger is suitable for easy and safe positioning of workpieces or components at stops and support points prior to clamping or assembly.

Locating pins of your own profile or design can be attached to our threaded pin types.

Material

Pin

• Steel, case-hardened, blackened

Body

· Steel, zinc-plated by galvanization

Grub Screw

· Steel, blackened, with brass pad

Mounting block

· Zinc die-cast, plastic coated, black


Knoh


· Steel, blackened


Lock nut

· Steel, blackened

Drawing













picture 1

picture 2

Erwin Halder KG

picture 3

picture 4

Order information


Dimensions										Stroke		ws	Spring	J load ¹⁾		I	Art. No.
d ₁	d ₂ d ₃	d ₅	d ₆	1 I ₂	I ₃ I ₄	-0.2	I ₆	I ₇ I	o 1	k s	WS ₁	WS ₂	F ₁	F ₂	max.		
[mm]									[mm]	[mm]	[]	N]	[°C]	[g]		
with prism – picture 4																	
•																	

¹⁾ statistical average value

www.halder.com Page 1 of 2

Published on: 3.2.2024

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

www.halder.com Page 2 of 2

Published on: 3.2.2024