# **Adjustable Tension Levers**

24440.0202



# **Product Description**

#### **Material**

#### Lever

· Steel, blackened

### Inner parts

• Steel, blackened, quality 5.8

#### Ball knob

• Thermosetting plastic PF 31, black, DIN 319

### **Operation**


By lifting the lever the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.


#### More information


#### **Notes**

The threaded portion can be exchanged.

# **Drawing**







### **Order information**

Dimensions										I	Art. No.
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	I	t	_	
								~	min.		
[mm]										[9]	
with female thread – picture 1, Steel											
24	M10	16	10	25	40	4.5	2.5	96	14	153	24440.0202

### Compliance

### **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

## Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

# **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Erwin Halder KG

# **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 1 of 1

Published on: 3.2.2024