Spring Plungers • with pin and slot - INCH 2B020.0266



Product Description

To be used for positioning, indexing, locking, latching as well as for other similar pressure applications.

Spring plungers can be used for locating or for applying pressure, as a detent or for ejection.

Material

Pin

• Free cutting steel, hardened, blackened

Body

· Free cutting steel, blackened

Spring

Stainless steel

Characteristic

Heavy spring load: marked with two lines





Standard spring load

Heavy spring load

More information

Notes

Special types on request.

Spring plungers are specially tested for spring range and forces.

This product is manufactured in INCH dimensions.

References


A conversion table can be found in the technical data following these product information pages. Thread lock: polyamide spot coating (for

details please refer to the technical appendix).

Further products

· Spring Plungers, with pin and slot

Drawing




Order information

Dimensions					Stroke	Spring	load ¹⁾			Ĭ	Art. No.
d	1	Thread	d₂	I	S	F ₁	F₂ ∼	min.	max.		
	[in]		[in]		[in]		b]	[°	F]	[oz]	
free cutting steel, heavy spring load, With thread lock											
#8-32	0.164	2A-UNC	0.07	7/16	0.052	1.8	4.6	-22	194	0.023	2B020.0266

1) statistical average value

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.