Index Plungers Compact • with hexagon collar

22110.0247



Product Description

Index plungers are used for indexing bores.

Types with / without lock have the same building height.

Due to a thread recess the index plungers can be completely screwed in.

Material

Body

• Stainless steel 1.4305

Locking pin

· Stainless steel 1.4305, nickel-plated

Assembly

The screw length can be adapted by distance collars for index plungers (EH 22120.).

More information

Notes


Knob not removable.

Lock nuts have to be purchased separately.

Further products

- Mounting Blocks, for index bolts and index plungers, die-cast
- Locating Bushings, for index bolts and index plungers
- Distance Collars, for index plungers

Drawing



Erwin Halder KG www.halder.com

Order information


Dimensions								ws	Sprir	ng load ¹⁾		I	Art. No.	
d₁	d ₂	l ₂	d ₄	d ₅	l ₃	I ₄	I ₅	I ₆		F ₁	F ₂	max.		
-0.02		min.								~	~			
-0.05														
[mm]									[mm]		[N]	[°C]	[g]	
without knob – picture 2, Stainless steel														
5	M10 x 1	8	M4	8	18	6	5.5	3	12	5	18	250	17	22110.0247

¹⁾ statistical average value

Accessories

	Dimensions d ₂	Wrench size	ă	Art. No.					
	[mm]	[mm]	[9]						
Lock nuts ISO 8675 (DIN 439), Stainless steel									
	M10 x 1	16	5.2	22120.0515					

Application example



Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Erwin Halder KG

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2

Published on: 3.2.2024