Index Plungers Compact • with hexagon collar, with T-Handle 22110.0928



Product Description

Index plungers are used for indexing bores. Simple handling, e.g. when using safety gloves, with higher pull release. Types with / without lock have the same building height. Due to a thread recess the index plungers can be completely screwed in.

Material

Body

Stainless steel 1.4305

- Locking pin
- Stainless steel 1.4305, nickel-plated

Knob

• Thermoplastic PA 6, black, dull

Assembly

The screw length can be adapted by distance collars for index plungers (EH 22120.).

More information

Notes


Knob not removable.


Lock nuts have to be purchased separately.

Further products

- Mounting Blocks, for index bolts and index plungers, die-cast
- Locating Bushings, for index bolts and index plungers
- · Distance Collars, for index plungers

Drawing





Order information


Dimensions							ws	Spring load ¹⁾		<u>.</u>		Ĭ	Art. No.
d₁ -0.02 -0.05	l ₂	d ₂	l ₁	I ₃	I4	I ₅		F ₁ ~	F ₂ ~	min.	max.		
[mm]							[mm]	[N]	Ì	[°C]	[g]	
Stainless steel													
10	12	M16 x 1,5	59	26	8	59	17	9.5	38	-30	80	66	22110.0928

1) statistical average value

Accessories

	Dimensions d ₂	Wrench size	ň	Art. No.					
	[mm]	[mm]	[g]						
Lock nuts ISO 8675 (DIN 439), Stainless steel									
	M16 x 1,5	24	15.0	22120.0518					

Application example



Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.