Index Plungers • with hexagon collar and locking

22120.0606



Product Description

Index plungers are used for indexing bores.

Material

Body

· Stainless steel 1.4305

Locking pin

· Stainless steel 1.4305, nickel-plated

Knob

· Thermoplastic PA 6, black, dull

Assembly

The screw length can be adapted by distance collars for index plungers (EH 22120.).

The knob is pulled-out, turned 90° and secured by a notched catch (when locking pin should not overhang).

More information


Notes

Knob not removable. Lock nuts have to be purchased separately.

Further products

- · Mounting Blocks, for index bolts and index plungers, die-cast
- Locating Bushings, for index bolts and index plungers
- Distance Collars, for index plungers

Drawing



Order information

Dimensions									Spring load ¹⁾				I	Art. No.
d ₁	d_2	d ₃	I ₁	l ₂	l ₃	I ₄	I ₅		F ₁	F ₂	min.	max.		
-0.02			~	min.			min.		~	~				
-0.05														
[mm]							[mm]	[N]		[°C]	[9]		
Stainless steel														
6	M12 x 1,5	25	61	6	20	6	17	14	6.5	19	-30	80	36	22120.0606


¹⁾ statistical average value

Erwin Halder KG www.halder.com Page 1 of 2 Published on: 3.2.2024

Accessories

	Dimensions ${\sf d_2}$	Wrench size	Ĭ.	Art. No.						
	[mm]	[mm]	[g]							
Lock nuts ISO 8675 (DIN 439), Stainless steel										
	M12 x 1,5	18	7.5	22120.0516						

Application example



Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2
Published on: 3.2.2024