Index Plungers • with pull-ring

22120.1312



Product Description

Index plungers are used for indexing bores.

Material

Body

· Steel, blackened

Locking pin

· Stainless steel 1.4305, nickel-plated

Pull-ring

Stainless steel 1.4310

Assembly

Lock nuts have to be purchased separately.

Operation


When using the model with locking mechanism, you turn the pull-ring by 90° after retracting the locking pin and secure the ring using the notched catch (if the locking pin should not overhang).

More information


Further products

- · Mounting Blocks, for index bolts and index plungers, die-cast
- Locating Bushings, for index bolts and index
- Distance Collars, for index plungers
- Mounting Blocks, for index bolts and index plungers

Drawing



picture 1



picture 2

Published on: 3.2.2024

Order information


Dimensions								Stroke	Spring load ¹⁾			I	Art. No.
d ₁	d ₂	d ₃	I ₁	l ₂	l ₃	I ₄	m	S	F ₁	F ₂	max.		
-0.05			min.						~	~			
-0.1													
[mm]								[mm]		[N]	[°C]	[g]	
without locking – picture 1, Steel													
5	M10 x 1	1.5	5	22	28	23	18	5	5	15	250	12	22120.1312

¹⁾ statistical average value

Accessories

	Dimensions d_2	Wrench size	ă	Art. No.					
	[mm]	[mm]	[g]						
Lock nuts ISO 8675 (DIN 439), Steel									
	M10 x 1	16	5.2	22120.0115					

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Erwin Halder KG

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2

Published on: 3.2.2024