Index Plungers • with pull-ring

22120.1420



Product Description

Index plungers are used for indexing bores.

Material

Body

· Stainless steel 1.4305

Locking pin

· Stainless steel 1.4305, nickel-plated

Pull-ring

Stainless steel 1.4310

Assembly

Lock nuts have to be purchased separately.

Operation


When using the model with locking mechanism, you turn the pull-ring by 90° after retracting the locking pin and secure the ring using the notched catch (if the locking pin should not overhang).

More information


Further products

- · Mounting Blocks, for index bolts and index plungers, die-cast
- Locating Bushings, for index bolts and index
- Distance Collars, for index plungers
- Mounting Blocks, for index bolts and index plungers

Drawing







with locking

picture 2

Published on: 3.2.2024

Order information


Dimensions								Stroke	Spring load ¹⁾			I	Art. No.
d ₁	d ₂	d ₃	l ₁	l ₂	l ₃	I ₄	m	S	F ₁	F ₂	max.		
-0.05			min.						~	~			
-0.1													
[mm]								[mm]		[N]	[°C]	[g]	
without locking – picture 1, Stainless steel													
8	M16 x 1,5	2	9	34	44	25	22	9	7	27	250	45	22120.1420

¹⁾ statistical average value

Accessories

	Dimensions d ₂	Wrench size	ă	Art. No.					
	[mm]	[mm]	[g]						
Lock nuts ISO 8675 (DIN 439), Stainless steel									
	M16 x 1,5	24	15.0	22120.0518					

Application example



Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Erwin Halder KG

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2

Published on: 3.2.2024