Lateral Plungers • with thread, without seal

22150.0355



Product Description

To be used for positioning and applying pressure, e.g. during painting and sandblasting.

Material

Body

• Steel, zinc-plated by galvanization

· Steel, blackened

Pin

· Steel, case-hardened, zinc-plated by galvanization

Assembly

Lateral plungers are installed by screwing in by means of a mounting tool.

Formula for calculating the center distance for the mounting hole:

 $I_0 = z/2 + w + x$

I₀ = center distance,

y = workpiece height,

w = workpiece length,

x = coordinate dimension,

s = stroke,

z = stop diameter

Calculation dimension x:

y greater than or equal to l_2 - $d_2/2$,

then $x = d_2/2 - s$


y smaller than l_2 - $d_2/2$,


then $x = d_2/2 - s - [(l_2 - d_2/2 - y) * 0,123]$

Characteristic

Version standard spring load = spring from steel, blackened

Drawing







Erwin Halder KG www.halder.com Page 1 of 2 Published on: 3.2.2024

Order information


Dimensions					Stroke	ws	<u>N</u>	I	Art. No.		
d ₁	I ₁ -2	Spring load F max. 1)	d ₂	l ₂	5		max.	•			
[mm]		[N]		[mm]	[mm]	[mm]	[°C]	[g]			
Pin: Steel/Standard spring load											
M18 x 1,5	31.5	150	10	16.9	3.2	16	250	29	22150.0355		

¹⁾ statistical average value

Accessories

assembly tool	Dimensions d ₁ [mm]	[e]	Art. No.
	M18 x 1,5	137	22150.0822

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2
Published on: 3.2.2024

Erwin Halder KG