Lateral Plungers • smooth, with seal

22150.0140



Product Description

To be used for positioning and applying pressure, e.g. during painting and sandblasting. Sealed against chips and dirt.

Material

Seal

• CR

Body

Aluminium Al

Spring

· Stainless steel

Pin

Steel, case-hardened, zinc-plated by galvanization

Assembly

Installation by pressing in.

Formula for calculating the center distance for the mounting hole:

 $I_0 = z/2 + w + x$

 I_0 = center distance,

y = workpiece height,

w = workpiece length,

x = coordinate dimension,

s = stroke,

z = stop diameter

Calculation dimension x:

y greater than or equal to l_2 - $d_2/2$,

then $x = d_2/2 - s$

or

y smaller than l_2 - $d_2/2$,

then $x = d_2/2 - s - [(l_2 - d_2/2 - y) * 0,123]$

Characteristic


Version light spring load = spring from stainless steel


More information

Further products

• Eccentric Mounting Bushings, for lateral plungers, smooth

Drawing





Order information

Dimensions		Spring load	ring load Dimensions		Stroke	Location hole	x ²⁾		Ĭ	Art. No.		
d₁	d ₂	max. 1)	l₁ -2	l₂ ±0.5	S	D H8		max.				
[mm]		[N]	[m	 m]	[mm]	[mm]	[mm]	[°C]	[g]			
Pin: Steel/pin from steel, light spring load												
16	10	100	18.5	16.4	1.6	16	3.1	110	15	22150.0140		

¹⁾ statistical average value

Erwin Halder KG




www.halder.com Page 1 of 2
Published on: 2.5.2024

 $^{^{2)}}$ If the workpiece height (y) is less than I2-d2/2, the coordinate dimension (x) must be calculated.

Accessories

	Dimensions d ₁ [mm]	[9]	Art. No.					
assembly tool								
	16	105	22150.0833					

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2
Published on: 2.5.2024