Lateral Plungers • with plastic spring and pin



Product Description

To be used for positioning and applying pressure, e.g. during painting and sandblasting.

Material

Spring

plastic

Pin

· Steel, case-hardened, blackened

Assembly

It is recommended to moisten the body.

Installation by pressing in.

Formula for calculating the center distance for

the mounting hole:

 $I_0 = z/2 + w + x$

 I_0 = center distance, y = workpiece height,

w = workpiece length,

x = coordinate dimension,

s = stroke,

z = stop diameter

Calculation dimension x:

y greater than or equal to l_2 - $d_2/2$,

then $x = d_2/2 - s$


y smaller than l_2 - $d_2/2$,

then $x = d_2/2 - s - [(l_2 - d_2/2 - y) * 0,123]$


Characteristic

Version light spring load = blue spring

Drawing







Order information

Dimensio	ons d ₂	Spring load F max. 1)	Dimer I ₁ -1	nsions I ₂ ±0.5	Stroke s	Location hole D H8	x ²⁾	max.	ă	Art. No. ³⁾		
[mm]		[N]	[m	m]	[mm]	[mm]	[mm]	[°C]	[g]			
Pin: Steel/pin from steel, light spring load												
6	3	10	7	3.7	0.2	5.9	1	100	0.5	22150.0200		

¹⁾ statistical average value

Erwin Halder KG

Page 1 of 2 Published on: 2.5.2024

^{*}some sizes (see chart) have a deviating pin shape

 $^{^{2)}}$ If the workpiece height (y) is less than I2-d2/2, the coordinate dimension (x) must be calculated.

³⁾ deviating pin shape (see drawing)

Accessories

assembly tool	Dimensions d ₁ [mm]	[9]	Art. No.
	6	23	22150.0840

Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

www.halder.com Page 2 of 2

Published on: 2.5.2024