Lateral Plungers • with plastic spring and pin 22150.0226



Product Description


Material Spring plastic Pin

· Stainless steel


To be used for positioning and applying pressure, e.g. during painting and sandblasting.

Assembly
It is recommended to moisten the body. Installation by pressing in. Formula for calculating the center distance for the mounting hole: $l_0 = z/2 + w + x$, $l_0 = center distance$, y = workpiece height, w = workpiece height, x = coordinate dimension, s = stroke, z = stop diameter Calculation dimension x: $y greater than or equal to l_2 - d_2/2$, then $x = d_2/2 - s$ or $y smaller than l_2 - d_2/2$, then $x = d_2/2 - s - [(l_2 - d_2/2 - y) * 0,123]$
Characteristic
Version standard spring load = red spring

Drawing







*some sizes (see chart) have a deviating pin shape

Order information

Dimensions d ₁ d ₂		Spring load F	Dimensions		Stroke s	Location hole D	x ²⁾	Janax.	Ĭ	Art. No.
[mm]		max. ¹⁾ ~ [N]	-1	±0.5	[mm]	H8 [mm]	[mm]	[°C]	[g]	
- · ·	Pin: Stainless steel/pin from stainless steel, standard spring load									
12	8	50	13	13.3	0.6	11.9	2.7	100	6.8	22150.0226

¹⁾ statistical average value

 $^{2)}$ If the workpiece height (y) is less than I2-d2/2, the coordinate dimension (x) must be calculated.

Accessories

assembly tool	Dimensions d ₁ [mm]	a [9]	Art. No.
	12	96	22150.0843

Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.