# Seating Pins ⋅ pin shape 22680.0484




# **Product Description**


To be used as solid and precise seat and stop. The pin-shaped form of this locating pin allows an application in components with narrow seating points.
Bearing surface induction hardened and grounded.

• Heat-treated steel, tempered, blackened

## **Drawing**









picture 1

Erwin Halder KG

picture 2


# **Order information**


Dimensions						ws	Tightening torque	I	Art. No.
I₁ ±0.01	d <sub>1</sub>	d <sub>2</sub>	l <sub>3</sub>	t	d <sub>3</sub>		max.	_	
[mm]						[mm]	[Nm]	[g]	
		_							
with female	thread – picture	2							


www.halder.com Page 1 of 2


Published on: 3.2.2024

# **Application example**









### Compliance

#### **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

# **Does not contain Proposition 65 substances**

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

# **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 2 of 2
Published on: 3.2.2024