# Horizontal Toggle Clamps · with horizontal base

23330.1503



## **Product Description**

Due to their favourable power to movement ratio and their easy action the toggle clamps are versatile applicable for a wide rang of uses.

These toggle clamps can be used in the metal working industry when drilling, welding, bending, grinding, testing and fitting as well as in the wood and plastic industry in glueing, drilling, cutting and milling jigs.

The "toggle" principle of the toggle clamp allows a large and quick opening of the clamp. If unclamped the workpieces are completely cleared for unimpeded removal. The large power transmission results maximum clamping force by low hand force. The clamps are self-arresting they remain locked, resisting the force produced when machining components.

The toggle clamps are manufactured from high quality components and are designed for continuous use.

A oil resistant ergonomic 2-component handle, with increased grip area with soft surface for high ease of use.

The quickly adjustable clamping screws are provided by a retainer.

#### Material

#### Clamp

· Stainless steel

#### Rivet

· Stainless steel

#### Handle

· plastic

## Clamping screw

- Steel, tempered, zinc-plated by galvanization
- · Stainless Steel

### Clamping cap


· Rubber, black

### More information

### References

Replacement clamping screws are available as accessories in the online shop.

## **Drawing**



Erwin Halder KG

www.halder.com

Page 1 of 4 Published on: 3.2.2024

Orde	Order information																												
Nomina	mina Clamping Dimensions										Но	ding	α		Į.	I	Art. No.												
size	screw												fo	rce				۲											
		d <sub>1</sub>	d <sub>2</sub>	b <sub>1</sub>	b <sub>2</sub>	b;	3	b <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	h₅ min.ı	<b>h</b> ₅ max		l <sub>2</sub>	I <sub>3</sub>	I <sub>4</sub>	<b>I</b> <sub>5</sub>	I <sub>6</sub>	I <sub>7</sub>	I <sub>8</sub>	F <sub>1</sub>	F <sub>2</sub>		min.	max.		
	[mm]	[mm]								[kN]			[°(	C]	[g]														
Stainless steel																													
3	M6 x 35	5.6	5.6	42	6	19.5 –	29.5	28.5	45	68	24	13.2	-1.5	5	162	64	16	32	38	6	26	12.7	1	1.2	90°	-10	80	189	23330.1503

# Accessories

Clamping screw (spare p	Dimensions  d <sub>2</sub> [mm]  part of toggle clamp), Stainless Steel	<b>[</b> g]	Art. No.
	M 6 x 35	16.0	23330.9503




www.halder.com Page 2 of 4
Published on: 3.2.2024

# **Application example**







# Compliance

## **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Erwin Halder KG

### Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

## **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 4 of 4

Published on: 3.2.2024