Tapered Shaft Hubs • with lock nut 25050.0108



Product Description

It is a self-centering and non-floating tapered shaft hub in corrosion-protected design with a hexagon nut and a lock nut.

The rotational accuracy of the tapered shaft hubs is 0,03 mm. By using tapered shaft hubs, all shaft-hub joints of machine elements such as sprocket wheels, gear wheels, belt pulleys, cams, levers etc. can be easily and efficiently established.

Material

External part

· Steel, zinc-plated by galvanization

Inner part

• Steel, nickel-plated

Nut

· Steel, nickel-plated

Assembly


The lock nut at the outer part facilitates locking of the shaft-hub joint if freely rotating shafts are involved. For mounting, a cresent wrench (thickness max. I_2 - I_3) is used.

More information

References

Comply with mounting instructions, mounting examples, and technical data.

Drawing



Order information


	Dimensions			WS	Tightening	Transferable	Transferable	Surface	Surface	Hub bore	Shaft diameter		Art. No.		
d₁	d	d ₂	4	I 2	I3		torque of	torque	axial load	pressure	pressure	D ₁	D ₂	-	
		-	.	-			the nut	м	Fa	of shaft	of hub	H9	h9		
							TA	max.	max.	pw	р _N				
							max.			max.	max.				
	[mm]			[mm]	[Nm]	[Nm]	[kN]	[N/mm²]	[N/mm²]	[mm]	[mm]	[g]			
8	1	4	22	17	11	16	16.9	23.4	5.8	179	121	14	8	21	25050.0108

Accessories

	WS [mm]	[9]	Art. No.			
special fork wrench						
~	16	72	25050.0816			

Application example





Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

