# **Rubber Endstop Buffers** • low structure



# **Product Description**

For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is 70 ±5° Shore A.

#### Material


#### Support washer

• Steel, zinc-plated by galvanization, passivated


#### Body

NBR

# **Drawing**








picture 2


### **Order information**

d <sub>1</sub>						Spring rate R	Load capacity max.	Spring range	min.	max.	ı	Art. No.
[mm]						[N/mm]	[N]	[mm]	[°C]		[g]	
with through-bore – picture 1												
32	4	5	9	2	1.1	1680	1680	1	-30	120	12	25150.1132

# **Application example**



Erwin Halder KG





Page 1 of 2 Published on: 3.2.2024

# Compliance

# **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

### Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

#### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Erwin Halder KG

www.halder.com Page 2 of 2

Published on: 3.2.2024