Rubber Endstop Buffers • low structure 25150.1250



Product Description

For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is 70 \pm 5° Shore A.

Material


Support washer


 Steel, zinc-plated by galvanization, passivated

Body

• NBR

Drawing







picture 2

Order information

Dimensionsd_1hd_2d_3s_1s_2+0.5+0.5+0.5					S ₂	Spring rate R	Load capacity max.	Spring range	min.	max.	Ĩ	Art. No.
[mm]						[N/mm]	[N]	[mm]	[°C]		[g]	
with through-bore and adhesive pad – picture 2												
50	5	6	11	2.5	1.1	3600	3600	1	-30	120	41	25150.1250

Application example





Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

